



# SERVICE BULLETIN 401

426 Industrial Boulevard • Kearneysville WV 25430-2776 • USA  
 Telephone: +1 304 728 7056 • technicalinquiry@royalvenders.com  
 Toll-free in North America: 1 800 931 9214 • Fax: +1 304 725 4016  
 Canada: +1 905 738 5777 • Mexico: +52 55 5203 6887  
 Europe: +49 2158 95 1000 • Australia: +61 2 9890 5433

Page: 1 of 1

Date: 20 Oct 2015

Revision: 01

**SUBJECT:** Coin Deflector Kit Installation

**MODELS:** GIII venders with Center Door Changer

Number of  
People  
Required



**KIT NUMBER**

**KIT DESCRIPTION**

161605

Coin Deflector Kit



The following areas of this vender contain voltage which can cause serious injury or even death: the main power cord, supplying 115-230 VAC to the evaporator, EMI filter, and refrigeration system; the power line from the EMI filter to the ballast and transformer; and the ballast, which can produce upwards of 600 volts. Remove all power from the vender before working in any of these areas.

**TOOLS REQUIRED:** Phillips screwdriver

**ESTIMATED INSTALLATION TIME:** <5 minutes

**PURPOSE:** This bulletin describes the procedure for installing the coin deflector kit in GIII venders with Center Door Changers.

## INSTALLATION INSTRUCTIONS:

1. Remove power by unplugging the vender's main power cord from the AC voltage source (wall outlet).
2. Remove the existing coin deflector from the vender's coin chute.
3. Attach the new coin deflector to the clip, using the screw from the kit. (See Figure 1.)
4. Install the new coin deflector assembly in the vender's coin chute. (See Figure 2.) Note: Proper hole installation will be dependent upon the specific brand and model of changer installed in the vender.
5. Restore power by plugging the vender's main power cord into the AC voltage source (wall outlet).

**Figure 1.** Attach the coin deflector and the clip with the screw, as shown here.

**Figure 2.** Install the coin deflector assembly on the coin chute as shown here.

Install the screw here.



coin deflector clip

coin deflector

coin chute installed assembly right-side mounting holes



The recommended location for both the coin deflector and the changer is the left set of mounting holes, as shown here. Certain changers or types of coinage may require the deflector or the changer to be installed in the right set of holes.

In an effort to provide our customers with the latest information on our equipment, Royal Vendors sends service bulletins to customers using the original ship-to address or e-mail addresses, if supplied by our customers. We also post all service bulletins on our website at [www.royalvenders.com](http://www.royalvenders.com). If for any reason a vender is moved to another location or is sold to another customer other than to whom Royal Vendors originally sent the machine, it is the responsibility of the original purchaser of the vender to notify the appropriate personnel of the service bulletin.

**ANY QUESTIONS? CONTACT ROYAL VENDORS' CUSTOMER SERVICE DEPARTMENT  
 IN NORTH AMERICA, CALL TOLL FREE 1 800 931 9214**